

LUBING

BREEDER DRINKER
THE STANDARD IN BREEDER DRINKERS



RELENTLESS QUALITY. EXCEPTIONAL SERVICE.

BREEDER PULLETS



Nipples per 10' Section - Standard
8 - 15 nipples per 10' (3 m) Section

Max. Recommended System Length
250' (80 m) per regulator

Water Pressure Requirement - 250' Length
Pressure regulator: min. 20 psi (1.380 bars)
max. 45 psi (3.103 bars)
Ball tank regulator: min. 20 psi (1.380 bars)
max. 45 psi (3.103 bars)

Nipple	Water Column	Side Flow (mL/min)	Vertical Flow (mL/min)
4077	8"	20-30	40-50
4078		20-30	40-50
4095		20-25	30-40

BREEDER PRODUCTION



Nipples per 10' Section - Standard
10 nipples per 10' (3 m) Section
12 nipples per 10' (3 m) Section
15 nipples per 10' (3 m) Section

Max. Recommended System Length
250' (80 m) per regulator

Water Pressure Requirement - 250' Length
Pressure Regulator: min. 20 psi
max. 45 psi


Nipple	Water Column	Side Flow (mL/min)	Vertical Flow (mL/min)
4071	8"	NA	40-50

WATERING SECTIONS INCLUDE:

- 10' (3 m) long, square, PVC, pipe
- Nipples with or without LitterGard cups
- Expansion coupler with stainless steel crimping rings
- 10' (3 m) aluminum support rail
- 4 plastic holding clips
- Galvanized connectors, 4 nuts and bolts
- 5 Hangers

DOUBLE WIRE HANGER

The double wire hanger is available for drinkers used without the electro-charger.



NOTE: Watering sections are shipped completely pre-assembled. Only galvanized connectors and hangers are not assembled. Ten complete sections are packed in one carton. Cartons are protected, carefully banded and shipped on skids.

